A STONE CARE SOLUTION

TECHNICAL DATA SHEET

MARBLE MAGIK DENSIFIER

Damp proof, water, dirt & a stain repellent providing surface consolidation for concrete, italian stone

Product Category : Sealer
Product Code : S225

PRODUCT DESCRIPTION

Marble Magik Densifier is an ecological water base treatment to solidify concrete or any stone and protect the surface from dirt, food, mould and mildew. Product is highly recommended for a porous surface and makes surface harden. Also used as an additive for concrete.

USES

- Use as densifier for marble floor
- Treated surface provide moderate stain proofing
- Use of Marble Magik densifier will provide a higher gloss on surface

FEATURES & BENEFITS

- Ecological
- Very good penetration and damp proof
- No stain penetration
- No film formulation
- Easy cleaning
- Nanotechnology prevent dust accumulation
- Chemical process required one time only
- Solidification of marble and concrete
- Vapor barrier remain as it is

SUITABLE SURFACE

- Marble
- Granite
- Natural stone
- Concrete

SURFACE PREPARATION

Ensure surfaces to be treated are dry, clean and free of residues. Floor should be properly grind with rough emery to make stone level and to open veins of stone for deep penetration of floor.

MIXING INSTRUCTION & APPLICATION

Mixing Instruction

Ready to use

Application Process

Clean Marble from any dirt or cement impurity with a jet of water. Allow it to fully dry. Finish one polishing step.Clean the polish surface with water and allow it to dry. Start to spread a thin layer of Marble Magik Densifier with floor wiper. Wait till the Marble Magik Densifier gets penetrated into marble. Repeat application after every drying. Apply Marble MAgik Densifier till fully saturation. Apply Marble Magik up to a uniform layer deposit on the marble surface. Allow it to cure for 48 hours or no.of days as per site requirement

Application Condition

- Residual moisture content of the stone substrate should not exceed 5%.
- No rising moisture & potential osmosis problems.
- Substrate temperature should be at least 3°C above dew point but not above 50°C.
- Recommended ambient temperature for application is between 10°C - 40°C.
- Relative Air Humidity (RH) to not exceed beyond 80%.

CLEANING

Required Residual traces of the product can be removed from tools with Magik EGFR before the product has hardened.

TECHNICAL DATA

Aspect	Nano Liquid
Colour	Clear to slightly hazy
pH	10 (5% in water)
Base	Water

CONSUMPTION

Any suitable surface	1 L - 3 to 4 sq.mt.

The data given is for guideline only. The physical values are subject to normal manufacturing tolerances, colour and testing variances. The coverage & consumption figures are theoretical and do not allow for any additional material required due to surface porosity, surface profile, variations in level or wastage etc.

PACKAGING

- 5 L
- 10 L
- 20 L

STORAGE & SHELF LIFE

Keep in a cool and well ventilated area.
For best result, use within 7 days from opening to avoid possible spoilage.
For product expiry information, please refer to the product packing.

ANNOTATION

- Porous & soft marble should be treated by both sides,to avoid stain and water mark which can be shown from topside after mirror finish of particular stone. Treat with Magik Back Coat from back side.
- Marble Magik Densifier should be treated upto over saturation.
- Cover the furniture and other articles with protective film to avoid staining the product while polishing.
- Always use good quality brush, sponge, scrubber or white cotton cloth while application to avoid damaging the surface due to the decolorization.
- While using any tools like spray pumps, low hand pressure pumps, water jets, mixer machines, grinding machines in application, clean the inner and outer surface of the tool to avoid any kind of damage to the surface and material to be used.

HEALTH & SAFETY

Precautions

- During application wear protective clothing, gloves and eye goggles during application. Avoid products to contact eyes and skin.
- Keep out of reach of children.
- Not for internal consumption.
- Apply between temp. 5°C to 35°C.
- Use only in well ventilated areas.
- Wash hands thoroughly after applying.

Accident

- Use water spray.

Spillage

- Take up mechanically or with absorbent material.

First Aid

- If swallowed, contact a physician.
- If in skin contact wash skin with water and remove contaminated clothing.
- If you come in contact with the eye, hold open, flood with water for at least 10 min and contact a physician.

NOTES

The information above is believed to be accurate and represents the best information currently available to Marble Magik Corporation. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the Marble Magik Corporation be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however arising, even if the company has been advised of the possibility of such damages. Users must always refer to the most recent issue of the local product datasheet.
Always test on a small area First and allow a 24 hour cure time to determine the ease of application and desire time.

Always refer to MSDS prior to using the product.

PRODUCT PHOTO

Corporate Office : Marble Magik Corporation, TF-418, Happy Hallmark Shoppers, Vesu Abhava Road, Surat-395017, Gujarat, India.
Call : +91 90999 88272
E-mail : info@marblemagik.com
Website : www.marblemagik.com

Version : 24.02.2021.01
Copyrights : Marble Magik Corporation. All rights reserved.

Please note that this datasheet supersedes all previous versions. For feedback or complaints, write to Marketing Manager Services on the above mentioned address.